



HD 28" FLOOR PLATE

2015-2017 FORD F-150

Installation Instructions

425-0032

425-0033




Instructions on back.



Lift up center console and remove OEM cup holder and set aside.



Remove the (2) T20 screws that were exposed.



Lift the plastic base from the center console, being careful to disconnect the wires from the rear of the base.



Remove (2) 18mm bolts from the rear of the OEM center seat.



Remove (2) 1/2" bolts from the front sides of seat.



Lean seat back and disconnect wire harness on P/S. Set seat aside.



Remove rear bracket from OEM sea, held in place by (3) 1/2" bolts. Reinstall OEM bracket back into vehicle re-using (2) OEM 18mm bolts, that were removed 3 steps earlier.



Loosely mount Floor Plate Feet, as marked on feet for location, onto sides of OEM brackets re-using (4) OEM 1/2" bolts.



Slide Floor Plate onto brackets and into position using provided hardware. Once into desired position secure all hardware.

If you have questions or need further assistance please call Technical Support: 1.877.455.6886



209 W. EASY ST., ROGERS, AR 72756 • JOTTOPUBLICSAFETY.COM • 2/25

Jotto Desk™ is a patented product and Registered Trademark of Assembled Products™ Corporation.
Specifications subject to change without notice.

050-0191-00

